

RUBIA XT 20W50



Data sheet

Multigrade oil for diesel engine

APPLICATIONS

- Developed for all Diesel engines, turbocharged or not, in severe service conditions in all seasons.
- Suited for extended drain intervals (up to 30 000 km according to manufacturers).

PERFORMANCES

International Specification

- API CF-4/SJ
- ACEA E2
- MIL-L-2104E

OEMs' Specification

- DAIMLER CHRYSLER MB page 228.1
- MAN 271
- VOLVO VDS
- CATERPILLAR TO-2

CUSTOMER BENEFITS

Performance profile

- Multigrade
- Very high viscosity index
- Excellent viscosity stability in operation
- Excellent detergency level
- High dispersancy level
- Excellent antiwear and anticorrosion properties
- Very good anti oxidant, antirust and antifoam properties

CHARACTERISTICS

Total Rubia XT	Method	Units	SAE Grade 20W50
Volumetric mass at 15°C	ASTM D1298	kg/m ³	895
Viscosity at 40°C	ASTM D445	mm ² /s	153
Viscosity at 100°C	ASTM D445	mm ² /s	17
Viscosity Index	ASTM D2270	-	120
Pour Point	ASTM D97	°C	-21
Flash Point	ASTM D92	°C	230
TBN	ASTM D2896	mgKOH/g	9.2

The typical characteristics mentioned represent mean values.

Total Rubia XT 20W50
Version Sept 2005

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.