

AURELIA XL 4030 Product name : Page : 1/6 SDS n° :32195-49 Version of :2007-06-13 Version :1.00 PRODUCT LABELS LABELLING (standard or EU): Concerned R-phrases : R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. S-phrases : S-61 Avoid release to the environment. Refer to special instructions/Safety Data Sheets. TRANSPORT LABELLING: Not applicable. 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING AURELIA XL 4030 Name of the product : JZ0 Code No. : Product application : Engine oil Supplier : TOTAL LUBRIFIANTS Le Diamant B 16, rue de la République 92922 Paris La Défense - France Tel: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71 Contact : HSE + 49 0 30/ 20 27 94 29 msds@total.de Giftnotruf Berlin BERLIN Tel. +49 30 19 240 Emergency telephones : See local details at end of sheet : 2. HAZARDS IDENTIFICATION Health effects : This product does not present a danger of intoxication. Environmental impact : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not discharge this product into the environment. Physico-chemical hazards : No special risk of fire or explosion under normal conditions of use 3. COMPOSITION/INFORMATION ON INGREDIENTS

PREPARATION

Chemical nature :Petroleum-derived severely refined mineral-base product in which the polycyclic aromatic hydrocarbons (PCA or PAH) content, measure IP 346, is less than 3%	ed by
--	-------

Substances presenting a health hazard	EC No.	CAS No.	Content	Symbol(s)	R-phrases
branched Alkylphenol and calcium branched chain alkylphenol			<0,5 %	Xn ,Xi ,N	R-38, 62, 50/53,Repr. Cat.3

See section 16 for explanations of R-phrases :

4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.



Product name :	AURELIA XL 4030	Page : 2/6
SDS n° :32195-49	Version :1.00	Version of :2007-06-13
Inhalation :	Inhalation of heavy concentrations of vapour, fur irritation of the throat. Transport the person into fresh air, keep warm at	
Ingestion :	Possible risk of vomiting and diarrhoea. Do not induce vomiting to avoid the risk of aspiration into the respiratory tract. Give nothing to drink	
Skin contact :	Immediately remove all soiled or stained clothing. Wash the affected area immediately and repeatedly with soap and water.	
Eye contact :	Keep eyes open and rinse immediately and repeatedly with water for at least 15 minutes.	
Aspiration :	If the product is believed to have entered the lun example), take the person to hospital for immedi	
5. FIRE FIGHTING MEASURES		
Flash point: See heading 9		
Extinguishing media :	 suitable: Foam, carbon dioxide (CO2), powder. not recommended: Do not use water jets (stick jets) for extinguishin of flames. 	g fire, as this may help the spread
Specific hazards :	Incomplete combustion and thermolysis may pro- as carbon monoxide, carbon dioxide, various hyd These may be highly dangerous if inhaled. Vapours can build explosive mixtures with air. Vapours are heavier than air and may spread on	drocarbons, aldehydes and soot.
Protective measures for firefighters :	Insulated breathing apparatus must be worn in co concentrations of fumes and gases.	onfined premises with heavy
Other :	All combustion residues and contaminated water disposed of according to local regulations.	from fire-fighting should be
6. ACCIDENTAL RELEASE MEASURES		
See sections 8 and 13.		
Personal protection :	Ensure good ventilation. Remove sources of ignition. Do not smoke.	
After spillage / leakage :	- On land: Surfaces on which the product has been spilled r Do not allow the product to enter sewers or river Recover with mechanical means such as pumps a On water	s or contaminate the soil.

7. HANDLING AND STORAGE

HANDLING :

Prevention of user exposure :	Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk. Make all the necessary arrangements in order to reduce exposure risk, notably to
	products in use or to wastes.
	Keep away from combustible substances; keep away from food and beverages.

presence of surface effluent.

Floating absorbant material, then mechanical recovery. If the product is spilt into rivers or sewers, notify the authorities of the possible

- On water:



Product name :	AURELIA XL 4030	Page : 3/6
SDS n° :32195-49	Version :1.00	Version of :2007-06-13
Prevention of fire and explosion :	Empty containers may contain flammable or exp There is a fire hazard associated with rags, paper remove spills which become soaked with produc Avoid accumulation of these: they are to be disp	r or any other material used to ct.
Precautions :	Avoid static electricity build up with connection to earth. Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for example).	
STORAGE :		
Technical measures :	Make the necessary arrangements to prevent wa	ter and soil pollution.
Storage precautions :	 Suitable: Store at room temperature, protected against cor away from any source of ignition. Keep containers closed when not in use To be avoided: Do not store exposed to the elements. 	ntact with water and moisture, and
Incompatible products :	Dangerous reaction with strong oxidizing agents	3.
Packaging materials :	- Recommended: Use only hydrocarbon-resistant containers, joint Keep in original container if possible.	s, pipes, etc.
Hazard class fire (Germany) :	В	
Storage class VCI (Germany) :	10	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures :	Use the product in a properly ventilated atmosphere. When working on enclosed place (tanks, reservoirs), make sure that atmosphere is not suffocating and/or wear recommended equipment.
Occupational exposure limit :	The product contains no relevant quantities of components with exposition limits for work that have to be supervised according to TRGS 900/901. . oil mist : 10mg/m3, for 15 minutes . oil mist : 5mg/m3, for 8 hours
Hand protection :	Impermeable hydrocarbon-proof gloves. recommended material: nitrile, neoprene. The break through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the break through times have to be found out from the manufacturer of the protective gloves themselves. The demands on the gloves are determined by the conditions in practice (e.g. multiple use, mechanical load, temperature, strength and duration of exposition). Before choosing suitable gloves, it is recommended that the user tests the gloves.
Eye protection :	Goggles, in case of risk of splashing.
Skin and body (other than the hands) protection :	As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when handling drums). Don't wear rings, watches or anything similar which can retain the product and may give rise to skin conditions.



Safety Data Sheet **AURELIA XL 4030** Page : 4/6 **Product name :** SDS n° :32195-49 Version :1.00 Version of :2007-06-13 Avoid prolonged and repeated contact with the skin, especially with used or waste Hygienic work practices : product Immediately remove all soiled or stained clothing. If the product comes into contact with the skin, wash the affected area immediately and copiously with soap and water. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. Do not eat, drink or smoke whilst handling the product. 9. PHYSICAL AND CHEMICAL PROPERTIES Appearance : Liquid. Colour: Light yellow to brown Odour · Characteristic. Density/specific gravity : 910 kg/m3 Temperature (°C) 15 Flash point : >= 230 °C (ASTM D 92) Température d'auto-inflammation : > 250 °C (ASTM E 659) Comments on autoignition temperature : This temperature may be significantly lower under particular conditions (slow oxidation on finely divided materials...). Pour point: < -12 °C (ASTM D 97) Solubility : - in water : Insoluble Soluble in many common solvents. Partition coefficient (log Pow) : Log Pow (Mineral oil) > 6Temperature (°C) 20 13.5 - 14.5 mm2/s Viscosity : Temperature (°C) 100 **10. STABILITY AND REACTIVITY** Stability : The product is stable at normal storage, handling and use temperatures. Conditions to avoid : Heat (temperatures above flash point), sparks, ignition points, flames, static electricity Materials to avoid : Avoid contact with strong oxidizers Hazardous decomp. products : Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. **11. TOXICOLOGICAL INFORMATION**

Acute toxicity / Local effect :Inhalation, comments:Not classified according to the criteria of classification in force.
Inhalation of high concentrations of vapour or aerosols may cause irritation of the
upper respiratory tract.Skin contact, comments:Not classified according to the criteria of classification in force.Ingestion, comments:In case of ingestion of small quantities, no important effect observed. in case of
ingestion of larger amounts: abdominal pain, diarrhea, ...

CHRONIC TOXICITY OR LONG-TERM TOXICITY :



Product name :	AURELIA XL 4030	Page : 5/0
SDS n° :32195-49	Version :1.00	Version of :2007-06-1
Skin contact :	Characteristic skin affections (oil blisters) may repeated exposure through contact with stained	
Sensitization :	To our knowledge, the product does not cause a	aggravated sensitivity.
Carcinogenicity :	During use in engines, contamination of oil with low levels of combustion produ occurs. Used motor oils have been shown to cause skin cancer in mice following repeate application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have seri effects in humans if the oil is thoroughly removed by washing with soap and wat	
12. ECOLOGICAL INFORMATION		
Comments about ecotoxicity :	Experimental data on the finished product are n Harmful to aquatic organisms, may cause long- environment.	
Mobility :	 Air: there is a slow loss by evaporation. Soil: Given its physical and chemical characteristics, mobility in the ground. Water: The product is insoluble; it spreads on the surfa 	
Persistence and degradability :	The product should offer slow biodegradability	
13. DISPOSAL CONSIDERATIONS		
Waste disposal :	Dispose of in a safe manner, in accordance with If need be, collection by an authorised waste co incineration at an approved installation.	
Waste class :	13 02 05 The waste classification is dependant on the con of disposal. The waste classification mentioned here represe waste producer is responsible for the correct spe specification of the waste classification should be authorised waste disposal company.	ents only a recommendation. The ecification of the waste. The
Disposal of contaminated packaging :	Proceed in compliance with the prevailing regu	lations.

Not concerned by the transport regulations below.

Road (ADR) / Rail (RID) :

Transport by barge (ADNR) :

Marine (IMO-IMDG):

Air (ICAO/IATA) :

15. REGULATORY INFORMATION

The product has to be labelled according to EC-directions / hazardous materials ordinance.

Risk phrases :

 $R\space{-}52/53$ Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



Safety Data Sheet **AURELIA XL 4030 Product name :** Page : 6/6 SDS n° :32195-49 Version :1.00 Version of :2007-06-13 S-61 Avoid release to the environment. Refer to special instructions/Safety Data Safety phrases : Sheets. EU directives : Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC). This product fulfills the requirements of the European directives : 76/769/EEC StörfallV: The product is not subject to the Decree about emergencies. Water Hazard classification (WGK) : WGK 2 - hazardous to waters Sonstige Vorschriften, Beschränkungen und Verbotsverordnungen : Regulations on spent oil (AltölV) §7: After use, this oil must be sent to a used oil collecting location. Incorrect disposal of used oil endangers the environment. Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. **INVENTORIES:** CANADA (DSL): All components on DSL, NDSL EUROPE (EINECS) : All components on EINECS inventory JAPAN (ENCS): All components on ENCS PHILIPPINES (PICCS): All components on PICCS USA (TSCA) : All components listed in TSCA AUSTRALIAN (AICS) : All components on AICS KOREA (ECL): All components on ECL CHINA : All components on IECSC **16. OTHER INFORMATION**

Explanations of R-phrases in section 2 :	R-38 Irritating to skin.Repr. Cat.3R-62 Possible risk of impaired fertility.R-50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.			
Revision date:	2007-06-13			
* Information revised since the previous version of the SDS :				
SDS No. :	32195			

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.