

MSDS

(Material Safety Data Sheet)

SECTION #1 PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME: TOTAL DACNIS SE 32, 46, 68, 100 and 150

CHEMICAL NAME AND SYNONYMS: MIXTURE

MANUFACTURER/SUPPLIER'S NAME:

TOTAL LUBRICANTS CANADA INC. 220, LAFLEUR LASALLE, QUEBEC H8R 4C9 Tel.: (514) 595-7579 or 1-800-463-3955

24 HOURS EMERGENCY: Call CHEMTREC 1-800-424-9300 or 703-527-3887

PRODUCT USE: Synthetic diester based lubricant for compressors

WHMIS CLASS AND DESCRIPTION -

These products are not regulated by the WHMIS.

SECTION #2 COMPOSITION/INFORMATION ON INGREDIENTS

NOM	%	No CAS

ADDITIONAL REGULATORY INFORMATION

- No hazardous ingredients as defined by the Canadian Hazardous Products Act (BILL C70) or by OSHA 29 CFR 1910.1200.
- Canadian DSL status: All ingredients are listed.
- * No components of this product have been found carcinogenic or potential carcinogen. Does not contain ingredients that are listed as carcinogenic or potential carcinogen by OSHA, IARC or the U.S. National Toxicology Program (NTP). This product or its components have no teratogenic or mutagenic effects known.

ΤΟΤΑ	L LUBRIFIANTS CA	NADA INC.	220, Ave Lafleur	LaSalle	Qc	H8R 4C9		Tél.: 418.522.4095	888.654,4095	Fax:	418.522.6717	
Tél.:	514.595.7579	800.463.3955	Fax: 514.367.5767				PICKERING (ON):	Tal.: 905.831.9569		Fax:	905.831.6240	

TLC DACNIS SE SERIES MSDS.doc

5/20/2011

SECTION #3 PHYSICAL DATA

PHYSICAL STATE AT 25°C BOILING POINT: POUR POINT: DENSITY (g/cm³ at 15°C): VAPOR PRESSURE (mm Hg at 20°C): VISCOSITY (cSt at 100°C): pH: EVAPORATION RATE: SOLUBILITY IN WATER: APPEARANCE ET ODOR:

Liquid > 250°C < -40℃ 0,95 to 0 Negligible

< -40°C 0,95 to 0,99 Negligible 5 to 20 No Object Negligible Negligible Yellowish to amber liquid with characteristic odor

SECTION #4 STABILITY AND REACTIVITY

STABILITY: CONDITIONS TO AVOID:

PRODUCTS TO AVOID: HAZARDOUS DECOMPOSITION PRODUCTS: POLYMERIZATION:

Stable Avoid excessive heat, open flames and formation of oil mist. Oxidizing agents, strong acids and bases. N/A Will not occur

SECTION #5 FIRE FIGHTING MEASURES

FLASH POINT (COC):	>200℃
FLAMMABILITY LIMITS IN AIR:	LEL: N/A
(% PER VOLUME)	UEL: N/A
AUTOIGNITION TEMPERATURE (\mathfrak{C}):	N/A
EXTINGUISHING MEDIA:	Foam, Dry chemical and CO ₂
HAZARDOUS COMBUSTION PRODUCTS:	Normal combustion products, CO and CO ₂ .
SPECIAL FIRE FIGHTING PROCEDURES:	Do not enter confined fire space without adequate protective clothing and an approved positive self-contained breathing apparatus. Use water to cool fire exposed containers.

	L LUBRIFIANTS C		220, Ave Lafleur	LaSalle	Qc	H8R 4C9	QUÉBEC;	Tél.: 418.522.4095	888.654,4095		418.522.67
Tél.:	514.595.7579	800.463.3955	Fax: 514.367.5767				PICKERING (ON)	Tal.: 905.831.9569		Fax:	905.831.63

SECTION #6 TOXICOLOGICAL INFORMATION

	SPECIES	LD ₅₀ ORAL	LD ₅₀ DERMAL	LC ₅₀ INHALATION	HRS		
	Rat	> 5000 mg/Kg	> 2000 mg/Kg	N/A			
INH	INHALATION: Prolonged exposure to high vapor concentration of this product can cause headache, dizziness and nausea. Short-term overexposure can cause an irritation to the respiratory passages. Exposure limit to the mist = 5 mg/m ³ (TLV/TWA, ACGIH).						
CON	CONTACT WITH EYES: This product should not cause eye irritation. Repeated and prolonged contact ma cause eye irritation.						
SKI	SKIN CONTACT: This product should not cause skin irritation. Prolonged and repeated contact wit this product can cause skin drying, which may result in skin irritation and dermatitis.						
ING	INGESTION: May cause nausea.						
SE	SECTION #7 ACCIDENTAL RELEASE MEASURES						
SPILL AND LEAK PROCEDURES: Eliminate all ignition sources. Stop leak only if safe to do so. Absorb residue or small spills with absorbent material and remove to non-leaking							

SECTION #8 HANDLING AND STORAGE

STORAGE AND HANDLING: Store in cool, dry, ventilated area, away from heat and ignition sources. Use good personal hygiene. Always keep the container close.

containers for disposal.

SECTION #9 EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION:	Mechanical ventilation is recommended.
RESPIRATORY PROTECTION:	If mist present, chemical cartridge respirator is recommended.
GLOVES:	Resistant gloves (Viton, Nitrile, Neoprene) are recommended when handling this material.
EYE PROTECTION:	Chemical safety goggles are recommended.
OTHER PROTECTION:	In confined spaces or where the risk of skin exposure is higher, resistant clothing or apron should be worn.

TOTAL LUBRIFIANTS CANADA INC.		220, Ave Lafleur	LaSalle	Qc	н	
Tél.:	514.595.7579	800.463.3955	Fax: 514.367.5767			

H8R 4C9 QUÉBEC:

 QUÉBEC;
 Tél.: 418.522.4095
 888.654.4095
 Fax:
 418.522.6717

 PICKERING (ON):
 Tal.: 905.831.9569
 Fax:
 905.831.8240

SECTION #10 DISPOSAL CONSIDERATIONS

FIRST AID

WASTE DISPOSAL METHODS: Consult relevant local authorities. Reclaim or dispose of at a licensed waste disposal company. Incinerate with approval of appropriate local authority.

INHALATION: Remove person to fresh air. See a physician if irritation persists.

- **CONTACT WITH EYES**: Flush immediately with water for at least 15 minutes.
- **CONTACT WITH SKIN**: Wash contaminated skin with mild soap and water. See a physician if irritation persists.
- **INGESTION**: This product has a low toxicity. May cause nausea and have a laxative effect. Do not induce vomiting. Contact an Anti-Poison Center (1-800-463-5060).

- **INHALATION**: Prolonged exposure to high vapor concentration of this product can cause headache, dizziness and nausea. Short-term overexposure can cause an irritation to the respiratory passages. Exposure limit to the mist = 5 mg/m³ (TLV/TWA, ACGIH).
- **CONTACT WITH EYES**: This product should not cause eye irritation. Repeated and prolonged contact may cause eye irritation.
- **SKIN CONTACT**: This product should not cause skin irritation. Prolonged and repeated contact with this product can cause skin drying, which may result in skin irritation and dermatitis.
- INGESTION: May cause nausea.

SECTION #13 ECOLOGICAL INFORMATION

ENVIRONMENTAL EFFECTS:

SECTION #11

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities.

BIODEGRADABILITY: NOT READILY BIODEGRADABLE.

TOTAL LUBRIFIANTS CANADA INC						
Tél.:	514.595.7579	800.463.3955				

220, Ave Lafleur LaS Fax: 514.367.5767

LaSalle Qc H8R 4C9

QUÉBEC: Tél.: 418.522.4095 PICKERING (ON): Tal.: 905.831.9569

i22.4095 888.654.4095 Fax: 418.522.6717 331.9569 Fax: 905.831.6240

TLC DACNIS SE SERIES MSDS.doc

SECTION #14 TRANSPORTATION INFORMATION

TRANSPORTATION (TDG)

SHIPPING NAME:	None
UN NUMBER:	None
CLASS DESCRIPTION:	None

SECTION #15 REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the Controlled Products. Regulations (CPR) and the MSDS contains all the information required by the CPR.

THIS PRODUCT IS NOT A WHMIS CONTROLLED SUBSTANCE.

DSL/NDSL Status: This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act. This product and/or all components are listed on the U.S. EPA TSCA Inventory.

Other Regulatory Status: No Canadian federal standard; however, for general discharge guidance, federal installations limited to 15 mg/L for total oil and grease. Provincial criteria are likely and should be requested when notifying provincial authorities.

SECTION #16 ADDITIONAL INFORMATION

Prepared by: Francis Bossé, Chemist

Revised on: 02 NOVEMBER 2009

We believe that technical information and recommendations contained herein to be reliable and accurate. However, we provide these data without warranty or guarantee of any kind, expressed or implied. We assume no responsibility for any loss, damage, or expense, direct or consequential, arising from the use of products described herein.

TOTAL LUBRIFIANTS CANADA INC. Tél.: 514.595.7579 800.463.3955 220, Ave Lafleur La Fax: 514.367.5767

LaSalle Qc H8R 4C9

QUÉBEC: Tél.: 418.522.4095 PICKERING (ON): Tal.: 905.831.9669

522.4095 888.854.4095 Fax: 418.522.6717 831.9569 Fax: 905.831.8240