

# HI PERF 4T SPECIAL



## Data sheet

Multigrade oil for 4-stroke motorcycle engines

### APPLICATIONS

High performance 4-stroke engines

- All types of high performance 4-stroke motorcycle engines of all cubic capacities, for intensive conditions of use whatever the season.
- Adapted for gear boxes lubrication and oil immersed clutches (no clutch slippage)

### PERFORMANCES

Specifications

- API SG
- JASO MA

### CUSTOMER BENEFITS

- Good resistance to oxidation
- High viscosity index
- Excellent viscosity stability in operation
- Very high level of detergency
- Very high level of dispersancy.
- Good anti-wear, anticorrosion, antirust and anti-foaming properties
- No risk of destructive pre-ignition

### CHARACTERISTICS

HI PERF 4T SPECIAL	Units	SAE Grade 20W-50
Volumetric mass at 15°C	Kg/m <sup>3</sup>	888
Viscosity at 40°C	mm <sup>2</sup> /s	162
Viscosity at 100°C	mm <sup>2</sup> /s	17.93
Viscosity index	-	122
Flash point Cleveland	°C	244
Pour point	°C	-21

The typical characteristics mentioned represent mean values.

HI PERF 4T SPECIAL  
14 May 2004

This lubricant, when used according to our recommendations and for the purpose for which is intended, presents no particular hazards. A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.